HAYWARD

EXPERT LINE

AquaRite® + NG (pH + temperature kit)

A B C D E F

As defined by EN 17645.
Go to report pages to see the complete detail by item.

TH TOTALLY HAYWARD

3 YEARS OF WARRANTY STANDARD + 4 TH 8000 HOURS Cell

MADE IN EU

NOT ONLY A SALT CHLORINATOR!! THE BRAIN OF YOUR SWIMMING POOL

- New design of control box to disinfect, control and regulate all your pool (including variable speed filtration pumps, heat pumps, lighting,...)
- **Clean water at all times:** save on chemicals and offers unrivalled bathing comfort
- **Transparent cell** to enable a visual check of the chlorine production
- New transparent probe holder to facilitate mounting and visual check
- **Control all your pool remotely** with WiFi/Ethernet (optional)
- **Temperature probe included**. Smart filtration mode and heat pump control pre configured

INCLUDED

- Cl Production
- Touch Screen 4.3"
- Up to 50W
- Salt water & Sea water compatible
- Standard
- Control of the 4 auxiliary outputs
- Control of filtration and VS pumps
- Modbus protocol

All your parameters are managed by a dedicated free **Hayward® Poolwatch app**

SCAN ME

AVAILABLE OPTIONS

Description	AQR-PL-SV16STNG	AQR-PL-SV22STNG	AQR-PL-SV33STNG	AQR-PL-SV50STNG
Redox kit	E-OPTION-REDOX (plastic premium probe) / EG (glass probe)			
Free chlorine amperometric probe	H-OPTION-CL			
Free chlorine membrane probe	H-OPTION-CL2			
Conductivity probe	I-OPTION-SAL			
WiFi module	RS4WI-OPTION-W			
Ethernet module	RS4NET-OPTION-L			
Detachable touch screen	CTS-OPTION-TS			
Detachable TFT screen	AQR-PLUS-PANL			
Empty tank detection	AQR-PLUS-CANNE			
Pool Terre	KV02			

NEW

New probe holder PVC transparent included

Flow switch included

pH kit as standard

Redox probe kit as standard

Temperature kit

Free amperometric probe

Free chlorine membrane probe

WATER TREATMENT

HAYWARD

EXPERT LINE

AquaRite® + NG (pH + temperature kit)

As defined by EN 17645.
Go to report pages to see
the complete detail by item.

YEARS OF WARRANTY
3 STANDARD 4 TH 8000 HOURS
Cell

MADE IN EU



AQUARITE®+ NG
(PH + TEMPERATURE KIT)

Description	AQR-PL-SV16STNG	AQR-PL-SV22STNG	AQR-PL-SV33STNG	AQR-PL-SV50STNG
Maximum production Cl_2/h	16 g/h	22 g/h	33 g/h	50 g/h
Display production	0-100%			
Salt concentration	From 3g up to 100g of NaCl			
Choice of languages	ES (Spanish) - EN (English) - FR (French) - DE (German) - IT (Italian) - TR (Turkish) - CS (Czech) - PT (Portuguese) NL (Dutch) - PL (Polish) - HU (Hungarian) - RU (Russian) - HR (Croatian) - HE (Hebrew) - ZH (Chinese)			
Average Pool volume	75 m³	100 m³	150 m³	200 m³
Display	4,3" touch screen			
Power supply	230 Vac 50/60 Hz			
Dimensions	270 x 220 x 115 mm			
Electronic box	Black Polycarbonate fireproof plastic			
Protective lid	White ABS fireproof plastic			
Output	15.5 A 7 v	18.5 A 6.5 V	15 A 9.5 V	15 A 12 V
Consumption	120 W	150 W	150 W	170 W
Main control outputs	Filtration / lighting / heating			
Additional control outputs	4 additional auxiliary relays, configurable by the user			
Self-cleaning	By polarity inversion			
Maximum temperature	45 °C			
Flow detection	Gas sensor + mechanical flow switch			Mechanical flow switch
Alarms	Low production / no flow / AL3 for pH injection / AL4 for cell configurable			

TRANSPARENT CELL

Description	AQR-PL-SV16STNG	AQR-PL-SV22STNG	AQR-PL-SV33STNG	AQR-PL-SV50STNG
Salt chlorination cell	4 monopolar titanium plates	5 monopolar titanium plates	7 monopolar titanium plates	10 monopolar titanium plates
Minimum flow rate	5 m³/h	7 m³/h	9 m³/h	9 m³/h
Plate dimensions	200 x 45 mm	200 x 45 mm	400 x 45 mm	400 x 45 mm
Cell mount material	Transparent PVC plastic			
Cell attachment	Threaded for easy cell mounting			
Flexible piping diameter	63 mm			
Cell dimensions	355 x 305 x 305 mm			520 x 305 x 305 mm
Cell cable	(3 x 4) x 1.5 m (extended cable available see spare part catalogue)			(2 x 4) x 1.5 m
Maximum pressure	4 kg/cm²			
Maximum temperature	45 °C			

WiFi module

Ethernet module

Detachable touch screen

Detachable TFT screen

Empty Tank detection

Complete your installation

Supply your filtration pump, salt chlorinator, heat pump, electric cleaner with **HPOWERPRO-P**