

AquaRite® Pro Touch

EXPERT LINE



YEARS OF WARRANTY
3 STANDARD **4TH** 8000 HOURS




As defined by EN 17645.
 Go to report pages to see the complete detail by item.

AN EVOLUTION OF SALT CHLORINATOR ACCORDING OUR TIME

- **Salt chlorinator combined with water treatment controls**
- Available also in **low salinity**
- Touch screen included
- **From 3,2 gr salt/L for standard salinity and from 1,2 gr salt/L for low salinity**
- **Transparent cell** with Hayward® T-Cell technology
- **Automatic and continuous pH and rX control**
- **Probe holder including prefilter of 65 microns.**

INCLUDED



TOUCH SCREEN INCLUDED

For easy and intuitive use



AQUARITE® PRO TOUCH

Description	AQR-PROT-T3	AQR-PROT-T9	AQR-PROT-T15	AQR-PROT-T3LS
Maximum production Cl ₂ /h	10 g/h	20 g/h	30 g/h	Equiv 10 g/h
Average pool volume	60 m ³	95 m ³	150 m ³	50 m ³
Salt concentration	From 3,2 g/L			From 1,2 g/L
Display	Touch screen (4,3") removable screen for remote installation			
pH control	Included with variable pH pump (1,5L/h - 7L/h)			
rX control	Included (rX gold sensor)			
Temperature	Included in the cell			
Superchloration mode	Included (24 hours)			
Manual adjustment of Cl	Configurable by gramage			
Cover detection	Configurable production level 0-100% depending on open or closed pool cover			
Flow switch	Mechanical with 3/4" connection			
Self cleaning	Reverse polarity every 360 min			
Protection	Flow switch			
Alarms	AL3 for pH injection / AL4 for cell configurable			
Control box dimensions	270 x 220 x 120			

AVAILABLE OPTIONS

Cleaning base	GLX-CELLSTAND
External temperature	T-OPTION-TEMP
Pool Terre	KV02
Empty tank detection	AQR-PLUS-CANNE



Transparent cell with Hayward® T-Cell technology



Double probe holder



Peristaltic pump



pH - ORP and Goldline probes



Empty Tank detection