HAYWARD

Salt & Swim® 2.0

As defined by EN 17645.
Go to report pages to see the complete detail by item.

YEARS OF WARRANTY
3 STANDARD 8000 HOURS
Cell

MADE IN EU

NEW GENERATION SALT CHLORINATOR

- **Salt chlorinator** covering a wide range of chlorine production: 8, 16, 22, 33 gr/h of chlorine
- Production configuration thanks to the **LED display**
- **Transparent cell** for visual checks on production. Gas detector included as standard
- Detection of presence of a pool cover for adjustment of chlorine production
- **Flow detector kit** included by default
- **5 levels possible** of chlorine production (20, 40, 60, 80, 100%)

INCLUDED

Precise and user-friendly controls thanks to the LED display Salt & Swim® 2.0 changes colour depending on the control selection made, in particular for chlorine production with or without a closed pool shutter.

BLUE
Chlorine generation

GREEN
Superchlorination activated

PURPLE
Pool shutter closed and programmable chlorine generation

Installation of the cell in piping

> Installation in a vertical position, on by-pass, at the highest point of the installations

Complete your installation...

...with **EASY-CHEM-SPH** and **EASY-CHEM-SRXGS**

	Description	SASV08CEU	SASV16CEU	SASV22CEU	SASV33CEU
SALT & SWIM® 2.0	Maximum production Cl_2/h	8 g/h	16 g/h	22 g/h	33 g/h
	Chlorine production	5 levels possible: 20, 40, 60, 80, 100%			
	Average pool volume	30 m³	75 m³	100 m³	150 m³
	Salt concentration	3 to 100 g/L			
	Display	LED light			
	Superchlorination mode	●	●	●	●
	Manual adjustment of Cl %	●	●	●	●
	Gas detector	●	●	●	●
	Cover detection	●	●	●	●
	Alarm	Salt level / flow			
	Closed pool cover detection	Yes			
	External redox control	Dry contact			
	Packaging dimensions	400 x 400 x 210 mm			
	Weight	9 kg	9 kg	10 kg	10 kg