HAYWARD

EXPERT LINE

YEARS OF WARRANTY

TH TOTALLY HAYWARD 3 STANDARD 5 TH

COMPRESSOR TITANIUM

EnergyLine Pro **All-Season**

THE HEATING SOLUTION, WHATEVER THE SEASON

- **Horizontal air flow**, the standard for a large part of the installations
- Specially designed for use in **all seasons** and in extreme conditions at temperatures as **low as -12°C**
- Wi-Fi module optional to keep the control wherever you are
- **The Inverter ventilator** adjusts its rotation speed according to the external conditions and operates on idle to provide a **super silent mode**
- **Real-time information** on an intuitive touch screen
- **Self-adaptive defrost system** to optimize defrost cycles
- **Reversible mode** by cycle inversion to provide the best experience when temperatures are at the highest by decreasing the water temperature to a comfortable level
- Sustainable thanks to **durable and high-quality selected materials**
- Built with **scroll compressor** for unbeatable performances
- **Ready to install package**, our heat pumps are delivered with a **winter cover**, an **anti-vibration pads kit**, a **condensate drain kit** and a user manual

Reversible · For inground pool · For commercial pool · Frontal · All season · Works up to -12° C · Wi-Fi module optional · R410 · Silent mode · Automatic defrosting

19 cm Touch screen for easier control.

Simplified electrical connection.



MODULE WI-FI SMARTBOX OPTIONAL

Download the EyesPool Connect app and connect your heat pump to a smartphone, tablet or PC to view the main informations and change the temperature, operating times and operating mode parameters in real time. **Code: HW26100051**

ENERGYLINE PRO ALL-SEASON

Description	Unit	ENP6MASCA	ENP6TASCA	ENP7TASCA	ENP8TAS	ENP9TAS	ENP10TAS
Power supply	-	220 V - 240 V ∿/1 ph/50 Hz	380 V - 415 V ∿/3 N/50 Hz				
Refrigerant fluid	-	R410A					
Global warming potential	GWP	2088					
Mass of refrigerant	kg	2.30	2.30	2.80	2.50	3.00	3.50
Carbon dioxide equivalence (1)	tCO_2eq	4.80	4.80	5.85	5.25	6.30	7.35
Heating capacity Air 15°C - Hr (2) 71% - Water 26°C	kW	17.8	18.2	23.4	24.6	30.5	36
Electrical power input	kW	3.70	3.70	5.15	5.00	6.10	6.50
Input current	A	16.2	7.7	9.7	9.8	11.6	13.3
Coefficient of performance	COP	4.8	4.9	4.6	4.8	5.1	5.5
Nominal water flow	m^3/h	6.6	6.6	8.0	9.3	11.5	13.5
Hydraulic connection (included)	mm	50					
Hydraulic head loss (max.)	kPa	7	7	18	11	16	14
Sound pressure level @1 m	dB(A)	73	73	75	74	75	72.5
Sound pressure level @10 m	dB(A)	45	45	47	43	44	41
Type of fan	-	DC inverter					
Number of fan(s)	unit	2					
Fan speed range	rpm	600 - 950	830 - 960	800 - 1050	600 - 960	600 - 1000	600 - 1050
Silent mode	-	Yes					
Fan speed (Silent mode)	rpm	600	830	800	600		
Type of compressor	brand	Sanyo	Copeland				
Winter cover (included)	ref.	HWX20000240112			HWX32015240004		HWX20000240208
L x W x H (3)	mm	1138 x 470 x 1264			1360 x 470 x 1280		1482 x 485 x 1480
Weight	kg	127	123	140	142	160	182
Recommended pool volume (4)	m^3	≤ 70		≤ 90	≤ 100	≤ 130	≤ 145

Performance as per French standard NF EN 14511, included in NF-414 certification standard.
(1) Carbon dioxide equivalence (expressed per tonne of CO_2 equivalent) is a quantity that describes, for a given mixture and amount of greenhouse gas, the amount of CO_2 that would have the same global warming potential (GWP), when measured over a specified timescale (generally, 100 years).
(2) Humidity.
(3) Net dimensions of the entire unit.
(4) For pools equipped with a heat retention cover during use from May to September.